

Exmark Lazer Z Diesel Zero Turn Mower 96" LZS88CDYM96RW0

Excellent Condition. Well maintained. Only 168 hours use.

Amazing machine. Ready to cut 10 acres an hour.

Available for less than half current retail

NOW \$29,000

Located South Central Pennsylvania

Call or Text (814)626-0026

Overview

For a variety of reasons, the redesigned diesel-powered Lazer Z zero-turns may be the right choice for your cutting needs. These machines make quick work of the largest, toughest jobs and raise the bar for cut quality, operator comfort, fuel efficiency and ease of handling. Our large 96-inch flex wing deck is capable of mowing over 9.5-acres per hour, making it the most productive mower Exmark has ever built.

Features

Improved Handling

The engine and radiator have been placed lower to the ground in the redesigned Lazer Z Diesel. This provides an even lower center of gravity leading to improved traction and a smoother ride.

Reduced Maintenance and Service

With an efficient and robust powertrain system, in addition to eliminating drive belts, these machines have less maintenance and longer service intervals. And the tool-less belt access and removable floor pan makes servicing easy.

Fuel Capacity

For longer work intervals, the Lazer Z Diesel has a 12.0-gallon capacity with two tanks. This will keep you mowing longer with fewer fill-ups.

Tire Size / Ground Speed

The 26" x 12"-12" drive tires allow you to reach speeds up to 12.5 mph on machines equipped with the 1.6 Liter Common Rail engine. The large drive tires also provide superior traction and handling, giving you the ability to manage diverse terrain and conditions.

Productivity

The robust engine power and large deck sizes make these mowers Exmark's most productive diesel machines ever. They are a great solution for airports, parks, universities, municipalities and other sizeable properties.

Hydraulic deck lift provides for easy cutting height adjustment and quick transport.

On-Board Intelligence

The next generation RED leverages the latest technologies to deliver increased machine efficiency, ease of use and durability. This technology provides users an increased ability to control mower power and efficiency with defined performance modes.

Specifications

- Blade Spindles - No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft, double row bearings, top and bottom, and splined blade driver.
- Drive Tires - 26x12-12, 6ply Multi Trac®
- Tractor Frame - Welded, heavy-duty 1.5" x 3" x 3/16" tubular steel.
- Steering Control - Hydraulically dampened twin levers, adjust fore and aft., also adjustable to 2 height positions. Adjustable dampeners (3 positions) to customize drive responsiveness.
- Front Caster Tires - 15 x 6.0-6, smooth-tread, semi-pneumatic.
- Parking Brake Lever actuated internal wet disc brake.
- Seat - Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.
- Electrical- 12-volt battery with 55-amp alternator.
- Standard Features - 12-volt plug-in, engine hour meter and cup holder
- Engine Brand - Yanmar Diesel
- Engine Model - 3TNV88C
- Engine Displacement - 1642cc (1.6L)
- Fuel System - Common Rail Diesel
- Engine Speed - 3,000 RPM
- Air Filter - Heavy-duty canister air filtration system with electronic vacuum sensor
- Fuel Type - Diesel
- Fuel Capacity 12-gallon (45.4-L), side fuel tanks
- Fuel Level Indicator - mechanical float type
- Drive - Hydro-Drive - Kanzaki KPS-18T Transmission, 16-quart oil capacity, spin-on filter. 18Cc shoe type pumps and 17.84 cubic inch Hydro-Gear HGM-18 motors, hydraulic oil cooler.
- Speed - Infinitely variable speed from 0-12.5 mph (20 kmph) forward, 0-7 mph (11 kmph) reverse.
- Carb Compliant - Yes
- Deck Lift - Hydraulic
- Safety Package - Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.
- ROPS - 2-post foldable ROPS standard with seat belt and latch.
- PTO Engagement - Integrated wet clutch system in transmission, connected to right angle gearbox on deck via drive shaft
- Drive Wheel Release - Allows unit movement without engine running.
- Casters - .50" thick caster yoke arms.
- Engine Spec - DTR5
- Width / Cutting Deck - 96"
- Deck Style Description - Full-floating UltraCut Rear Discharge Deck. Rear-discharge standard with finish cut baffles and mulch kit included.
- Deck Construction - 7-gauge high strength alloy top that is formed and continuously seam welded, with 7-gauge high strength alloy side skirt.
- Blade Tip Speed - Approximately 18,500 fpm
- Cutting Heights - 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments.
- Blades - 4 Blades at 24.50" Length
- Width - 101.2 in. (257.0cm), 72.5 in. @3 in. HOC when folded
- Length - 97.2 in. (246.9 cm)
- Height - 71.8 in. (182.4 cm) with ROPS Up
- Curb Weight - 2650 lbs